



ESTIA UPS

3 Phase Input - 3 Phase Output / 10 - 60 kVA

NEW
PRODUCT

- On-Line "Double Conversion" technology
- IGBT Rectifier & Inverter
- Real DSP (Digital Signal Processor) Controlled Processor
- High Input Power Factor (PFC > 0.99)
- High Efficiency
- Low Input Current Harmonics (THDi < 3%)
- Low Output Voltage Harmonics (THDv < 1.5%)
- Easy-use LCD Display
- Energy Saving Mode (ECO Mode)
- Cold Start
- Wide Frequency and Voltage Range
- Smart Battery Management Software & Deep Discharge Protection
- Automatic Battery Test Feature
- Adjustable Battery Quantity (10-20kVA)
- External Battery Support for Long Backup time (External Battery Version)
- Battery Recharge Support with High Current (up to 9A)
- Standard built-in Static and Manual Bypass
- Short circuit and Overload Protection
- Built-in Back Feed Protection
- Temperature Controlled Smart Fan Speed Regulation
- Frequency Converter Operation Mode Selection
- Generator Compatible Operation
- Advanced Event Log
- Statistical Daily Data Log
- Comprehensive Communication Options
- Standard: RS-232, USB, EPO, GENSET, STS Sync
- Optional: SNMP, Relay Card, Modbus
- Two Years Full Warranty in accordance with ISO 9001, ISO 14001, CE standards
- INFORM 7/24 Technical Support and Customer Services



Estia

TECHNICAL SPECIFICATIONS

MODEL	ESTIA 33010	ESTIA 33015	ESTIA 33020	ESTIA 33030	ESTIA 33040	ESTIA 33060
Capacity (kVA/kW)	10kVA / 9kW	15kVA / 13,5kW	20kVA / 18 kW	30kVA / 27kW	40kVA / 36kW	60kVA / 54kW
INPUT						
Phase Number	3Ph + N + PE					
Nominal Voltage	380 / 400 / 415 VAC					
Voltage Range (VAC) (100% Load)*	[-15%] [+20%]					
Voltage Range (VAC) (50% Load)*	[-45%] [+20%]					
Frequency	50/60 Hz ±10% (Auto Sensing)					
Input Power Factor	>0.99					
Input Current Harmonics (THDi) **	<3%					
OUTPUT						
Output Power Factor	0.9					
Phase Number	3Ph + N + PE					
Nominal Voltage	380 / 400 / 415 VAC (Adjustable from LCD menu)					
Voltage Harmonics (THDv) **	< 1.5% [Linear Load], <3% [Nonlinear Load]					
Frequency	50Hz or 60Hz (Adjustable from LCD menu)					
Frequency Tolerance	Utility Mode: Rated frequencies ±1% ±2% ±4% ±5% ±10% Battery Mode: (50/60±0.2%)Hz					
Voltage Regulation	±1%					
Crest Factor	3:1					
Transfer Time	Online-Battery : 0ms; Online-Bypass: 0ms					
Overload*	10 minute at 125% load, 1 minute at 150% load					
Efficiency*	Up to 93%					
STATIC BYPASS						
Static Bypass Voltage Tolerance	380/400/415 VAC (Adjustable from LCD menu -15% +12%)					
Static Bypass Frequency Tolerance	47 Hz - 53 Hz (Adjustable)					
BATTERY						
Battery Connection	One String			Two Strings (with central neutral point)		
Type	Maintenance-Free Dry Type					
Recharge Time (For Internal Battery)	4-6 hours up to 90%					
Battery Qty (Compact Standard Bat.)	16x12V 9 Ah 32x12V 9 Ah	24x12V 9 Ah	32x12V 9 Ah	-		
Battery Qty (Compact External Bat.)	16-32 pcs (on request)	24-32 pcs (on request)	32 pcs	-		
Battery Qty (Tower Internal Bat.)	64x12V 9 Ah		62x12V 9 Ah		124x12V 9 Ah	
Battery Qty (Tower External Bat.)	16-32 pcs (on request)	24-32 pcs (on request)	32 pcs	62 pcs		
Recharge Current (Max.)	max. up to 9A (Adjustable)					
Cold Start (Start-up without mains)	Present					
ALARMS						
Audible & Visual	48 type alarms (Details can be found in User manual)					
Event Log	1024 pcs					
DISPLAY						
Indicator LED & LCD	Online mode, Bypass mode, Battery Low, Overload & UPS Failure					
LCD Display	Input Voltage, Current & Frequency, Output Voltage, Current & Frequency, Output power values (KVA, KW), Load Power Factor (PF), Load Rate, Battery Voltage & Current, Battery backup time, Bypass Voltage & Frequency, Output Current, Crest Factor, Internal Temperature					
PROTECTION						
	Overload, Short circuit, High Temperature, Battery Deep Discharge					
COMMUNICATION ***						
	Standard:RS232, USB, EPO, GENSET, STS SYNC Optional: SNMP, Dry Contact, Modbus (RS485)					
ENVIRONMENT CONDITIONS						
Operation Temperature Range	0°C - 40°C (20°C - 25°C recommended temperature for long battery life)					
Storage Temperature	-25°C - +55°C (15 - 40°C recommended temperature for long battery life)					
Humidity	0 - 95% (non-condensing)					
Operational Altitude	1500 meter					
Noise Level (from 1m distance)*	<55dBA					
Protection Class	IP20					
PHYSICAL SPECIFICATIONS						
Dimensions (mm) (WxDxH) Compact	295x620x875			-		
Dimensions (mm) (WxDxH) Tower	389x800x1170			506x800x1326		
Weight (w/o battery) [Compact]	48 kg	54 kg		-		
Weight (with 12V 9Ah) [Compact]	16 Blocks 88 kg 32 Blocks 128 kg	24 Blocks 114 kg	32 Blocks 134 kg	-		
Weight (w/o battery) [Tower]	87 kg	96 kg	100 kg	107 kg	138 kg	156 kg
Installation Type	Floor, Wheeled (Tower)					
STANDARDS						
	EN 62040-1(Safety), EN 62040-2 (EMC), EN 62040-3 (VFI-SS-111)					

* Depending on rated power and load rate at the output

** Depending on UPS power and environmental conditions

*** Please contact with your sales representative for communication options.

INFORM reserves the right to change the information contained herein without notice